

EXCELITE
Long Life List

Part No.	Market Designation	Range	ECE	SAE	Volt V	Watt W	Base	Test Volt V	Max. Watt W	Lumen Output Lm
10103	H1	LL	•	•	12	55	P14.5s	13.2	68	1550±15%
10203	H1	LL	•		24	70	P14.5s	28	84	1900±15%
10303	H3	LL	•	•	12	55	PK22s	13.2	68	1450±15%
10403	H3	LL	•		24	70	PK22s	28	84	1750±15%
10503	H4	LL	•		12	60/55	P43t	13.2	75/68	1650/1000±15%
10603	H4	LL	•		24	75/70	P43t	28	85/80	1900/1200±15%
10703	H7	LL	•	•	12	55	PX26d	13.2	58	1500±10%
10803	H7	LL	•		24	70	PX26d	28	75	1750±10%
10903	H8	LL	•	•	12	35	PGJ19-1	13.2	43	800±15%
11003	H8B	LL	•	•	12	35	PGJ19-1	13.2	43	800±15%
11103	H9	LL	•	•	12	65	PGJ19-5	13.2	73	2100±10%
11203	H9B	LL	•	•	12	65	PGJ19-5	13.2	73	2100±10%
11403	H11	LL	•	•	12	55	PGJ19-2	13.2	62	1350±10%
11603	H11	LL	•		24	70	PGJ19-2	28	80	1600±10%
11503	H11B	LL	•	•	12	55	PGJ19-2	13.2	62	1350±10%
11803	H13 9008	LL	•	•	12	60/55	P26.4t	13.2	75/68	1700/1100±15%
12003	H16	LL	•		12	19	PGJ19-3	13.2	26	500+10%/-15%
12103	H18	LL	•	•	12	65	PY26d-1	13.2	69	1700±8%
12203	HB1 9004	LL		•	12	65/45	P29t	12.8	70/50	1200/700±15%
12303	HB2 9003	LL	•	•	12	60/55	P43t	12.8	72/65	1500/910±10%
12403	HB3 9005	LL	•	•	12	60	P20d	13.2	73	1860±12%
12503	HB3A 9005XS	LL	•	•	12	60	P20d	13.2	73	1860±12%
12603	HB4 9006	LL	•	•	12	51	P22d	13.2	62	1095±15%
12703	HB4A 9006XS	LL	•	•	12	51	P22d	13.2	62	1095±15%
12803	HB5 9007	LL		•	12	65/55	PX29t	12.8	70/60	1350/1000±15%
13003	HIR2 9012	LL	•	•	12	55	PX22d	13.2	63	1875±15%
13603	H27W/1 880	LL	•		12	27	PG13	13.2	31	477±15%
13703	H27W/2 881	LL	•		12	27	PG13	13.2	31	477±15%